



# nCELL-F2240

5G NR Femtocell

2 x 2 MIMO 2 x 250 mw 128 RRC Subscribers

The nCELL-F2240 from BTI is an enterprise-level 5G integrated Femtocell applying 5G NR technology. The product connects to the backbone network through wired backhaul and provides 5G access for terminals. It supports the transmission of voice and data with indoor wireless broadband coverage.



## **KEY FEATURES**

- Integrated design of baseband and radio head
- Based on 3GPP R16 technology with high-speed data and low latency services
- Supports up to 100 MHz bandwidth
- 35W low power consumption
- Convenient networking, plug and play solution, easy and flexible deployment
- Plentiful security service provides real-time protection, to prevent potential security risks and illegal intrusion
- Web-based management, convenient and intuitive
- Complete network management function
- Humanized indicator light, easy to observe and manage equipment status
- IP3X protection level

## **APPEARANCE**







HARDWARE SPECIFICATION	NS
Work Style	5G SA
Working Frequency	SKU1: N41(2496-2690Mhz)
Working Bandwidth	40/60/80/100Mhz
<b>Transmit Power</b>	2 x 24 dBm
frequency Error	± 0.1 ppm
Sensitivity	< -96 dBm
EVM	64QAM/256QAM, ≤5%
ACLR	≤-45dBc
Synchronization	Support GPS, 1588v2
MIMO	2 x 2
<b>Equipment Size</b>	200 x 200 x64mm(L x W x H)
Installation Method	Wall hanging, ceiling
Power Consumption	< 45W
Power Supply	12V DC/10A



Weight	< 1.5 kg
Operating Temperature	-10 °C ~ +40 °C

SOFTWARE SPECIFICATIONS		
Technical Standard	3GPP Release 16	
Peak Rate (100 MHz Bandwidth)	7D2U: DL: 810 Mbps (256QAM)/ 3U1D: UL: 480 Mbps (64QAM)	
Operational Capacity	128 Subscribers	
Scheduling Method	3GPP standard QCI	
Network Management Interface	Supports TR069 interface protocol	
MTBF	5 Years	
MTTR	< 1 hour	
	Remote/local maintenance, based on SSH protocol	
	Online status management	
	Performance statistics	
	Fault management	
O&M	Configuration management	
	Local or remote software upgrade and loading	
	Supports log	
	Connectivity diagnosis	
	Self-start and self-configuration deployment	
	Alarm reporting	
	Supports KPI reporting	
	User information tracking	

#### **FCC Statement**

Please take attention that changes or modification not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

#### **RF Exposure Information**

This device has been tested and meets applicable limits for Radio Frequency (RF) exposure.

This equipment must be installed and operated in accordance with provided instructions and the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be colocated or operating in conjunction with any other antenna or transmitter.

This device must be professionally installed.



Contact Us Today www.btiwireless.com sales@btiwireless.com